

Device list

TOYOPUC-PCS

Device	Name		Specification	Type	CSA/UL	CE	*
CPU	CPU		Memory 12K words Built-in SN-I/F(Communication with TPYOPUC-PC3 JG/PC10)	TAC-6089	○	○	
Input /output module	Input module	DI001	8 points (for Cat.4 : 4 points). dry contact input 24VDC	TAK-6090	○	○	
		DI003	24 points (for Cat.4 : 12 points) dry contact input 24VDC	TAK-6104	○	○	
	Output module	DO002	4 points (for Cat.4 : 2 points). semiconductor output 24VDC 0.25A /point +	TAK-6093	○	○	
		DO003	4 points (for Cat.4 : 2 points). semiconductor output 24VDC 0.25A /point +	TAK-6108	○	○	
	Input module for a light curtain	SPM002	8 points (Cat.4 : 4 points) 24VDC (-) common type (PNP output type for light curtain connection)	TAK-6177	○	○	
Communication module	S-BUS		Safety communication Master	TAU-6098	○	○	
	RMT-S		Safety communication remote Slave	TAU-6102	○	○	
Base	BASE5		5 slot base	TAR-6148	○	○	
	BASE8		8 slot base	TAR-6149	○	○	
	BASE12		12 slot base	TAR-6094	○	○	
Power supply filter	P-FLT		Power supply filter for CPU, RMT-S	TAU-6207	○	○	
Fan unit 2	FAN2		Cooling fan for CPU, RMT-S	TAU-6208	○	○	
Cover	BLANK		Cover for empty slot protection	TAU-6211	○	○	